

IFE-EC

Ear Clamps



www.ife-group.com



IFE-EC or ear clamps are widely used across many industries including marine, beverage dispensing, irrigation, building, and automotive. The clamps are constructed with all stainless steel. Since they are a single range hose clamp they have a small working range and they need to be sized carefully. The underside of the band is designed so it maintains continuous contact around 360° surface of hose. This clamp is installed with a special pincer tool that is available in manual or pneumatic versions.

- more than 100 different sizes tooled and available
- clamp generates 360 contact with hose, no steps for leak paths
- manual or pneumatic installation tools available
- AISI 304 stainless steel is standard material but can be supplied in 316 stainless if ordered in sufficient quantities.



IFE Americas is a global provider of sealing and retaining solutions to meet customer needs. We offer a wide range of clamps, couplings, straps, and sleeves, with in-house testing facilities and technical support.



IFE-EC: Ear Clamps



www.ife-group.com

Specifications

IFE Part Number	Material Code 4		Material Thickness	Clamp Range	IFE Part Number	Material Code 4		Material Thickness	Clamp Range	IFE Part Number	Material Code 4		Material Thickness	Clamp Range
	Ear Width (mm)	Band Width (mm)				Ear Width (mm)	Band Width (mm)				Ear Width (mm)	Band Width (mm)		
144 124 2004 0065	3.7	5	0.50	5.3-6.5	144 124 2004 0256	10	7	0.60	22.4-25.6	144 124 2004 0725	10	7	0.60	69.3-72.5
144 124 2004 0070	3.7	5	0.50	6.0-7.0	144 124 2004 0271	10	7	0.60	23.9-27.1	144 124 2004 0740	10	7	0.60	70.8-74.0
144 124 2004 0080	4	5	0.50	6.7-8.0	144 124 2004 0286	10	7	0.60	25.4-28.6	144 124 2004 0755	10	7	0.60	72.3-75.5
144 124 2004 0087	5.5	5	0.50	7.0-8.7	144 124 2004 0301	10	7	0.60	26.9-30.1	144 124 2004 0770	10	7	0.60	73.8-77.0
144 124 2004 0095	5.5	5	0.50	7.8-9.5	144 124 2004 0308	10	7	0.60	27.6-30.8	144 124 2004 0785	10	7	0.60	75.3-78.5
144 124 2004 0100	5.5	5	0.50	8.3-10.0	144 124 2004 0316	10	7	0.60	28.4-31.6	144 124 2004 0800	10	7	0.60	76.8-80.0
144 124 2004 0105	5.5	5	0.50	8.8-10.5	144 124 2004 0331	10	7	0.60	29.9-33.1	144 124 2004 0815	10	7	0.60	78.3-81.5
144 124 2004 0113	5.5	5	0.50	9.6-11.3	144 124 2004 0346	10	7	0.60	31.4-34.6	144 124 2004 0830	10	7	0.60	79.8-83.0
144 124 2004 0118	5.5	5	0.50	10.0-11.8	144 124 2004 0361	10	7	0.60	32.9-36.1	144 124 2004 0845	10	7	0.60	81.3-84.5
144 124 2004 0119	8	7	0.60	9.4-11.9	144 124 2004 0376	10	7	0.60	34.4-37.6	144 124 2004 0860	10	7	0.60	82.8-86.0
144 124 2004 0123	8	7	0.60	9.8-12.3	144 124 2004 0381	10	7	0.60	34.9-38.1	144 124 2004 0875	10	7	0.60	84.3-87.5
144 124 2004 0128	8	7	0.60	10.3-12.8	144 124 2004 0396	10	7	0.60	36.4-39.6	144 124 2004 0890	10	7	0.60	85.8-89.0
144 124 2004 0133	8	7	0.60	10.8-13.3	144 124 2004 0411	10	7	0.60	37.8-41.1	144 124 2004 0905	10	7	0.60	87.3-90.5
144 124 2004 0138	8	7	0.60	11.3-13.8	144 124 2004 0425	10	7	0.60	39.3-42.5	144 124 2004 0920	10	7	0.60	88.8-92.0
144 124 2004 0140	8	7	0.60	11.5-14.0	144 124 2004 0440	10	7	0.60	40.8-44.0	144 124 2004 0935	10	7	0.60	90.3-93.5
144 124 2004 0145	8	7	0.60	12.0-14.5	144 124 2004 0455	10	7	0.60	42.3-45.5	144 124 2004 0950	10	7	0.60	91.8-95.0
144 124 2004 0148	8	7	0.60	12.3-14.8	144 124 2004 0470	10	7	0.60	43.6-47.0	144 124 2004 0965	10	7	0.60	93.3-96.5
144 124 2004 0153	8	7	0.60	12.8-15.3	144 124 2004 0485	10	7	0.60	45.3-48.5	144 124 2004 0980	10	7	0.60	94.8-98.0
144 124 2004 0157	8	7	0.60	13.2-15.7	144 124 2004 0500	10	7	0.60	46.8-50.0	144 124 2004 0995	10	7	0.60	96.3-99.5
144 124 2004 0162	8	7	0.60	13.7-16.2	144 124 2004 0515	10	7	0.60	48.3-51.5	144 124 2004 1010	10	7	0.60	97.6-101.0
144 124 2004 0166	8	7	0.60	14.1-16.6	144 124 2004 0530	10	7	0.60	49.8-53.0	144 124 2004 1025	10	7	0.60	99.3-102.5
144 124 2004 0168	8	7	0.60	14.3-16.8	144 124 2004 0545	10	7	0.60	51.3-54.5	144 124 2004 1040	10	7	0.60	100.8-104.0
144 124 2004 0170	8	7	0.60	14.5-17.0	144 124 2004 0560	10	7	0.60	52.8-56.0	144 124 2004 1055	10	7	0.60	102.3-105.5
144 124 2004 0175	8	7	0.60	15.0-17.5	144 124 2004 0575	10	7	0.60	54.3-57.5	144 124 2004 1070	10	7	0.60	103.8-107.0
144 124 2004 0178	8	7	0.60	14.5-17.8	144 124 2004 0590	10	7	0.60	55.8-59.0	144 124 2004 1085	10	7	0.60	105.3-108.5
144 124 2004 0180	10	7	0.60	14.8-18.0	144 124 2004 0605	10	7	0.60	57.3-60.5	144 124 2004 1100	10	7	0.60	106.8-110.0
144 124 2004 0185	10	7	0.60	15.3-18.5	144 124 2004 0620	10	7	0.60	58.8-62.0	144 124 2004 1115	10	7	0.60	108.3-111.5
144 124 2004 0192	10	7	0.60	16.0-19.2	144 124 2004 0635	10	7	0.60	60.3-63.5	144 124 2004 1130	10	7	0.60	109.8-113.0
144 124 2004 0198	10	7	0.60	16.6-19.8	144 124 2004 0650	10	7	0.60	61.8-65.0	144 124 2004 1145	10	7	0.60	111.3-114.5
144 124 2004 0210	10	7	0.60	17.8-21.0	144 124 2004 0665	10	7	0.60	63.3-66.5	144 124 2004 1160	10	7	0.60	112.8-116.0
144 124 2004 0226	10	7	0.60	19.4-22.6	144 124 2004 0680	10	7	0.60	64.8-68.0	144 124 2004 1175	10	7	0.60	114.3-117.5
144 124 2004 0235	10	7	0.60	20.3-23.5	144 124 2004 0695	10	7	0.60	66.3-69.5	144 124 2004 1190	10	7	0.60	115.8-119.0
144 124 2004 0241	10	7	0.60	20.9-24.1	144 124 2004 0710	10	7	0.60	67.8-71.0	144 124 2004 1205	10	7	0.60	117.3-120.5

Due to our program of continuous improvement, specifications may be subject to change.

IFE Americas USA

12877 Emerson Drive, Suite 200
Brighton, MI 48116
Phone: +1 (248) 446-1900
E-mail: info@ife-group.com

IFE Americas México

Bernardo Quintana 7001 Torre 2 – 813
Col. Centro Sur. Querétaro, Qro. 76090
Phone: +52 (442) 245-1515
E-mail: info@ife-group.com

IFE Europe Sweden

Banérgatan 51
SE-115 22 Stockholm
Phone: +46 708 102 711
E-mail: info@ife-group.com

